


Specifications:
 Current Rating:1.5A AC/DC
 Voltage Rating:30V AC/DC
 Contact Resistance:30m ohm. Max.
 Insulation Resistance:1,000M ohm. min.
 Withstanding Voltage:500V AC For One Minute
 Operating Temperature Range:-40°C ~ +105°C
 Material and Finish **-55 ~85°C**
 Insulator:PBT (UL94V-0)
 Insulator Color:White
 Contact:Brass **Phosphor Bronze**
 Plating:Gold Flash Plated in Contact Area,
 Tin Plated on Solder Tail.
 Shell:Brass,Nickel Plated



PCB layout

Note: Dimension in red represents old dimension

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.20 ±0.38 .XX=±0.15 ±0.25	<h1 style="text-align: center; color: red;">CnC Tech</h1> <p style="text-align: center;">Industrial Cable and Connector Technology</p>		
				CHECKED:	UNIT: MM			DESCRIPTION:
					SCALE:1:1	USB A Type PCB Socket Right Angle,G/F		A4
	05-FEB-2020			APPROVAL:	SHEET: 1 / 2			
REV	DATE	FILE	BY		PROJECTION:	1001-001-01000		

A
B
C
D