



Specifications:
 Current Rating:1.5A AC/DC
 Voltage Rating:30V AC/DC
 Contact Resistance:20m ohm. Max. **30m**
 Insulation Resistance:1,000M ohm. min.
 Withstanding Voltage:750V AC For One Minute **500V**
 Operating Temperature Range:-40°C ~ +105°C
 Material and Finish **-55°C~85°C**
 Insulator:PBT (UL94V-0) **PBT+30%GF**
 Insulator Color:Black
 Terminal:Brass **Gold flash and tin over nickel plated**
 Plating:30u" Gold Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:Brass,Nickel Plated
SPCC

Note: Dimension in red represents old dimension

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.20 ±0.30 .XX=±0.15	CnC Tech Industrial Cable and Connector Technology		
				CHECKED:	UNIT: MM			DESCRIPTION: USB A Type Plug Housing Reverse Type, 30 u"
					SCALE:1:1			A4
	05-FEB-2020			APPROVAL:	SHEET: 1 / 2	PART NO:		
REV	DATE	FILE	BY		PROJECTION:	1002-015-01001		

A

B

C

D