



Specifications:
 Current Rating:
 1.5A for VBUS and GND Contacts
 0.25A for all other Contacts
 Low Level Contact Resistance:30m ohm. Max.
 30m ohm(max) initial for VBUS and GND Contacts
 50m ohm(max) initial for all other Contacts
 Insulation Resistance:100M ohm. Min.
 Withstanding Voltage:AC 500V r.m.s
 Operating Temperature Range:-40°C To +105°C
 Materials:
 Insulator:PBT (UL94V-0)
 Insulator Color:Blue
 Contact:Phosphor Bronze
 Plating:15u" Gold Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:Copper Alloy
 Plating:Nickel Plated

Note: Dimension in red represents old dimension

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.25 .XX=±0.15	<h1 style="text-align: center; color: red;">CnC Tech</h1> <p style="text-align: center;">Industrial Cable and Connector Technology</p>		
				CHECKED:	UNIT: MM			DESCRIPTION:
					SCALE:1:1	USB 3.0 R/A Type Receptacle 15u"		A4
	05-FEB-2020			APPROVAL:	SHEET: 1 / 2			
REV	DATE	FILE	BY		PROJECTION:	1003-001-01000		