



**Specifications**  
 Current Rating: 3Amp  
 Insulation Resistance: 1000M $\Omega$  Min.  
 Dielectric Withstanding: 600V AC/DC  
 Contact Resistance: 20m $\Omega$  Max.  
 Operating Temperature: -40°C to +105°C

**Materials**  
 Contact Material: Copper Alloy  
 Insulation Material: Polyester, UL 94V-0  
 P.B.T  
 Contact plating: Gold Flash

All materials must be GP materials

NUMBER OF POSITIONS	Dimensions		
	A	B	C
10	32.00	21.84	10.16
14	37.08	26.92	15.24
16	39.62	29.46	17.78
20	44.70	34.54	22.86
26	52.32	42.16	30.48
30	57.40	47.24	35.56
34	62.48	52.32	40.64
40	70.10	59.94	48.26
50	82.80	72.64	60.96
60	95.50	85.34	73.66
64	100.58	90.42	78.74

# Cnc Tech, LLC

Industrial Cable and Connector Technology

<b>DESIGN</b>	<i>lumayc</i>	<b>PART NO.</b>	3010-XX-001-11-00	
<b>DATE</b>	2011.12.05	<b>REV</b>	A	<b>SIZE</b>
<b>CHECKED</b>		<b>UNIT</b>	mm	A4
			<b>UNLESS OTHERWISE SPECIFIED TOLERANCES</b> ANG 0 ±5° .0 ±0.3 .00 ±0.15 ±0.10	