



NUMBER OF POSITIONS	Dimensions		
	A	B	C
10	32.00	21.84	10.16
14	37.08	26.92	15.24
16	39.62	29.46	17.78
20	44.70	34.54	22.86
26	52.32	42.16	30.48
30	57.40	47.24	35.56
34	62.48	52.32	40.64
40	70.10	59.94	48.26
50	82.80	72.64	60.96
60	95.50	85.34	73.66
64	100.58	90.42	78.74

**Specifications**

Current Rating: 3amp  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding: 600V AC/DC  
 Contact Resistance: 20mΩ Max.  
 Operating Temperature: -40°C to +105°C

**Materials**

Contact Material: Copper Alloy  
 Insulation Material: Polyester, UL 94V-0 P.B.T  
 Contact plating: Gold Flash  
 All materials must be GP materials

# CnC Tech, LLC

Industrial Cable and Connector Technology

DESIGN	<i>Lawryc</i>	PART NO.	3010-XX-002-11-00	
DATE	2011.12.05	REV	A	SIZE
CHECKED		UNIT	MM	
<small>UNLESS OTHERWISE SPECIFIED TOLERANCES</small> ANG 0 ±.5° .0 ±0.3 .00 ±0.15 ±0.10				