

CnC Tech

Product change note:

FLAT Ribbon Cables

**MULTI-COLOR FLAT RIBBON CABLE:
304-28-XX-MC-XXXXF**

Changes:

D/C prior to 19/43

after D/C 19/43

CoO: CHINA

TAIWAN

UL2651

UL20029

Conductor Diameter: 0.381mm

0.39mm +/-0.05mm

Diameter: 0.9mm +/- 0.1mm

0.9mm +/- 0.05mm

Spark Test: -

3000V/0.15 Sec. Min.

Insulation Resistance: 100MΩ/Km 20°C

75MΩ/Km 20°C

General Tolerance:

.X = +/- 0.3

.X = +/- 0.2

.XX = +/- 0.15

.XX = +/- 0.15

**GRAY FLAT RIBBON CABLE
302-28-XX-GR-XXXXF**

Changes:

D/C prior to 19/36

after D/C 19/36

CoO: CHINA

TAIWAN

Construction: 7/0.12 +/-0.003mm

7/0.127 +/-0.005mm

Conductor Diameter: 0.36mm

0.39mm +/-0.05mm

Min Thickness: 0.23mm

0.21mm

E Marking: E332441

E315658

Insulation Resistance: **100MΩ/Km 20°C**

75MΩ/Km 20°C

General Tolerance:

.X = +/- 0.2

.X = +/- 0.2

.XX = +/- 0.25

.XX = +/- 0.15

CnC Tech

GRAY FLAT RIBBON CABLE

300-30-XX-GR-XXXXF

Changes:

D/C prior to 19/36

after D/C 19/36

CoO: CHINA

TAIWAN

Construction: 7/0.1 +/-0.005mm

7/0.102 +/-0.005mm

Conductor Diameter: 0.36mm

0.39mm +/-0.05mm

Material: PVC

POLYVINYL ??

Min Thickness: 0.15mm

0.6 mil

Max Thickness: 0.18mm

-

Average Thickness: -

0.7 mil

Diameter: 0.66 +/- 0.08mm

0.66 +/- 0.05mm

E Marking: E332441

E315658

Cond. Resistance: 337Ω/Km 20°C

361 Ω/Km 20°C

Insulation Resistance: 100MΩ/Km 20°C

1 G Ω !! /Km 20°C

General Tolerance:

.X = +/- 0.3

.X = +/- 0.2

.XX = +/- 0.15

.XX = +/- 0.15