


PCB layout



Specifications:

Current Rating: 1.5A AC/DC
 Voltage Rating: 30V AC/DC
 Contact Resistance: 30m ohm. Max.
 Insulation Resistance: 1,000M ohm. min.
 Withstanding Voltage: 500V AC For One Minute
 Operating Temperature Range: -40°C ~ +105°C
 Material and Finish
 Insulator: PBT (UL94V-0)
 Insulator Color: White
 Contact: Brass
 Plating: 30u" Gold Plated on Contact Area
 Tin Plated on Solder Tail.
 Shell: Brass, Nickel Plated

Note: Dimension in red represents old dimension

RoHS Compliant

| | | | | | | | | |
|-----|------|------|----|-----------|-------------------------------------------------------------|--------------------------------------------------------------|--------------------------------------------------------|-------------------|
| | | | | DRAWN: | GENERAL TOLERANCE: .X = ±0.20 ±0.38 .XX = ±0.10 ±0.25 | CnC Tech Industrial Cable and Connector Technology | DESCRIPTION: USB A PCB Socket Straight, 30u" | SIZE A4 |
| | | | | CHECKED: | UNIT: MM SCALE: 1:1 | | | |
| | | | | APPROVAL: | SHEET: 1 / 2 | PART NO: | 1002-021-01000 | |
| REV | DATE | FILE | BY | | PROJECTION: | | | |