



Specifications
 Current Rating:3.0A AC/DC 1A
 Voltage Rating:250V AC/DC
 Contact Resistance:20m ohm. Max
 Insulation Resistance:1000M ohm. Min
 Withstanding Voltage:600V AC For one minute 500V
 Operating Temperature Range : -40°C to +105°C

Material:
 Plastic:PBT (UL94V-0)
 Standard Color:Black
 Contact:Copper Alloy Brass
 Plating:Gold Plated Flash Gold

MATING PART
3030-XX-0103-00



MATING PART
3030-XX-0104-00



Notes:
 60P、64P With Three Key
 All Other Pin With One Key

Circuits	Dim					
	A	prior 20/06	B	prior 20/06	C	prior 20/06
10	32.20	32.00	10.16	10.16	-	27.94
14	37.28	37.08	15.24	15.24	-	33.02
16	39.82	39.62	17.78	17.78	-	35.56
20	44.90	44.70	22.86	22.86	-	39.70
24	49.98	49.78	27.94	27.94	-	45.72
26	52.52	52.32	30.48	30.48	-	48.26
30	57.60	57.40	35.56	35.56	-	53.34
34	62.68	62.48	40.64	40.64	-	58.42
40	70.30	70.10	48.26	48.26	-	66.04
50	83.00	82.80	60.96	60.96	-	78.74
60	95.70	95.50	73.66	73.66	-	91.44
64	100.78	100.58	78.74	78.74	-	96.72

Note: Dimension in red represents old dimension

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	<h1 style="text-align: center;">CnC Tech</h1> <p style="text-align: center;">Industrial Cable and Connector Technology</p>		
				CHECKED:	UNIT: MM			DESCRIPTION:
					SCALE:1:1	2.54mm Shrouded Header With Ejector Straight Type	A4	
	05-FEB-2020			APPROVAL:	SHEET: 1 / 1	PART NO:		
REV	DATE	FILE	BY		PROJECTION:	3010-XX-001-13-00		