



CNC part number	ITEM DESCRIPTION	IP	Thread	Cable range	Cable Range AWG	C1 - Thread O.D.	C2 - Thread Length	Spanner Size	L - Total Length	C3 - Max Diameter	L1 - Length above Panel
6001M8-4.8-001	Cable Gland, M8-4.8, BLACK	68	M8*1.25	2-4.8	20-16	8	7.5	12/13	26.4	13.6	19.5
6001M8-4.8-012	Cable Gland, M8-4.8, GRAY	68	M8*1.25	2-4.8	20-16	8	7.5	12/13	26.4	13.6	19.5
6001M10-6-001	Cable Gland, M10-6, BLACK	68	M10*1.5	3-6	18-14	10	8	15/13	28.7	17	20.4
6001M10-6-012	Cable Gland, M10-6, GRAY	68	M10*1.5	3-6	18-14	10	8	15/13	28.7	17	20.4
6001M12S-6-001	Cable Gland, M12S-6, BLACK	68	M12*1.5	3-6.5	18-14	12	8.5	18/15	30.8	19.3	21.8
6001M12S-6-012	Cable Gland, M12S-6, GRAY	68	M12*1.5	3-6.5	18-14	12	8.5	18/15	30.8	19.3	21.8
6001M12-8-001	Cable Gland, M12-8, BLACK	68	M12*1.5	4-8	16-12	12	8.5	18/19	35.6	21.4	27.1
6001M12-8-012	Cable Gland, M12-8, GRAY	68	M12*1.5	4-8	16-12	12	8.5	18/19	35.6	21.4	27.1
6001M16S-8-001	Cable Gland, M16S-8, BLACK	68	M16*1.5	4-8	16-12	16	10	22/19	40.4	24	26.5
6001M16S-8-012	Cable Gland, M16S-8, GRAY	68	M16*1.5	4-8	16-12	16	10	22/19	40.4	24	26.5
6001M16-10-001	Cable Gland, M16-10, BLACK	68	M16*1.5	5-10	14-10	16	10	22/22	39.6	25	29.6
6001M16-10-012	Cable Gland, M16-10, GRAY	68	M16*1.5	5-10	14-10	16	10	22/22	39.6	25	29.6
6001M18-10-001	Cable Gland, M18-10, BLACK	68	M18*1.5	5-10	14-10	18	10	24/22	37.5	25.7	27.4
6001M18-10-012	Cable Gland, M18-10, GRAY	68	M18*1.5	5-10	14-10	18	10	24/22	37.5	25.7	27.4
6001M20S-12.5-001	Cable Gland, M20S-12.5, BLACK	68	M20*1.5	6-12.5	12-8	20	10	27/24	39.6	29.2	30.6
6001M20S-12.5-012	Cable Gland, M20S-12.5, GRAY	68	M20*1.5	6-12.5	12-8	20	10	27/24	39.6	29.2	30.6
6001M20-14-001	Cable Gland, M20-14, BLACK	68	M20*1.5	8.5-14	10-6	20	11	27/27	44.86	29.24	33.7
6001M20-14-012	Cable Gland, M20-14, GRAY	68	M20*1.5	8.5-14	10-6	20	11	27/27	44.86	29.24	33.7
6001M22-14-001	Cable Gland, M22-14, BLACK	68	M22*1.5	8.5-14	10-6	22	11	30/27	45.2	33	34.1
6001M22-14-012	Cable Gland, M22-14, GRAY	68	M22*1.5	8.5-14	10-6	22	11	30/27	45.2	33	34.1
6001M24-14-001	Cable Gland, M24-14, BLACK	68	M24*1.5	8.5-14	10-6	24	11	30/27	41.3	32.9	31.1
6001M24-14-012	Cable Gland, M24-14, GRAY	68	M24*1.5	8.5-14	10-6	24	11	30/27	41.3	32.9	31.1
6001M25-18-001	Cable Gland, M25-18, BLACK	68	M25*1.5	12.5-18	8-4	25	11.6	33/33	49.5	36.2	36.1
6001M25-18-012	Cable Gland, M25-18, GRAY	68	M25*1.5	12.5-18	8-4	25	11.6	33/33	49.5	36.2	36.1
6001M30-20-001	Cable Gland, M30-20, BLACK	68	M30*1.5	17-20	6-3	30	12.5	37/35.5	50.3	40.2	39.9
6001M30-20-012	Cable Gland, M30-20, GRAY	68	M30*1.5	17-20	6-3	30	12.5	37/35.5	50.3	40.2	39.9

6001M32-25-001	Cable Gland, M32-25, BLACK	68	M32*1.5	17-25	6-2	32	15	41/42	55.4	45.6	43.3
6001M32-25-012	Cable Gland, M32-25, GRAY	68	M32*1.5	17-25	6-2	32	15	41/42	55.4	45.6	43.3
6001M36-25-001	Cable Gland, M36-25, BLACK	68	M36*1.5	18-25	6-2	36	12	45/42	54.6	49.3	43.3
6001M36-25-012	Cable Gland, M36-25, GRAY	68	M36*1.5	18-25	6-2	36	12	45/42	54.6	49.3	43.3
6001M40-31-001	Cable Gland, M40-31, BLACK	68	M40*1.5	23-32	4 – 1/0	40	15	50/52	63.8	58	49.5
6001M40-31-012	Cable Gland, M40-31, GRAY	68	M40*1.5	23-32	4 – 1/0	40	15	50/52	63.8	58	49.5
6001M50-41-001	Cable Gland, M50-41, BLACK	68	M50*1.5	30-41	2 – 2/0	50	15	62/62	74.9	67.1	53.4
6001M50-41-012	Cable Gland, M50-41, GRAY	68	M50*1.5	30-41	2 – 2/0	50	15	62/62	74.9	67.1	53.4
6001M63-45-001	Cable Gland, M63-45, BLACK	68	M63*1.5	35-45	1/0 – 3/0	63	18	75/65	85.1	81.5	58.2
6001M63-45-012	Cable Gland, M63-45, GRAY	68	M63*1.5	35-45	1/0 – 3/0	63	18	75/65	85.1	81.5	58.2
6001M75-66-001	Cable Gland, M75-66, BLACK	68	M75*2.0	56-66	4/0 – 300 kcmil	75	25	92/92	85.3	101.4	60.9
6001M75-66-012	Cable Gland, M75-66, GRAY	68	M75*2.0	56-66	4/0 – 300 kcmil	75	25	92/92	85.3	101.4	60.9
6001M90-77-001	Cable Gland, M90-77, BLACK	68	M90*2.0	66-77	300 – 500 kcmil	90	25	110/110	85.9	120.8	62.2
6001M90-77-012	Cable Gland, M90-77, GRAY	68	M90*2.0	66-77	300 – 500 kcmil	90	25	110/110	85.9	120.8	62.2

Note: Cable outer diameter to AWG conversion is for reference only. Actual conductor size may vary depending on insulation thickness and cable construction.



CNC part number	ITEM DESCRIPTION	IP	Thread	Cable range	Cable Range AWG	C1 - Thread O.D	C2 - Thread Length	Spanner Size	L - Total Length	C3 - Max Diameter	L1 - Length above Panel
6007S-6-12.5-001	Cable Gland, PG7S-6,BLACK	68	PG7	3-6.5	18-14	12.5	8	17/15	35.6	21.4	21.9
6007S-6-12.5-012	Cable Gland, PG7S-6,GRAY	68	PG7	3-6.5	18-14	12.5	8	17/15	35.6	21.4	21.9
6007-5-12.5-001	Cable Gland, PG7-5,BLACK	68	PG7	3-5.5	20-16	12.5	8	17/19	39.0	21.5	26.6
6007-5-12.5-012	Cable Gland, PG7-5,GRAY	68	PG7	3-5.5	20-16	12.5	8	17/19	39.0	21.5	26.6
6007-8-12.5-001	Cable Gland, PG7-8,BLACK	68	PG7	4-8	16-12	12.5	8	17/19	39.0	21.5	26.6
6007-8-12.5-012	Cable Gland, PG7-8,GRAY	68	PG7	4-8	16-12	12.5	8	17/19	39.0	21.5	26.6
6009-5.5-15.2-001	Cable Gland, PG9-5.5,BLACK	68	PG9	3-5.5	20-16	15.2	8.2	22/19	37.0	24.0	26.7
6009-5.5-15.2-012	Cable Gland, PG9-5.5,GRAY	68	PG9	3-5.5	20-16	15.2	8.2	22/19	37.0	24.0	26.7
6009-8-15.2-001	Cable Gland, PG9-8,BLACK	68	PG9	4-8	16-12	15.2	8.2	22/19	37.0	24.0	26.7
6009-8-15.2-012	Cable Gland, PG9-8,GRAY	68	PG9	4-8	16-12	15.2	8.2	22/19	37.0	24.0	26.7
6011-7-18.6-001	Cable Gland, PG11-7,BLACK	68	PG11	3-7	18-14	18.6	10	24/22	38.5	25.7	28.6
6011-7-18.6-012	Cable Gland, PG11-7,GRAY	68	PG11	3-7	18-14	18.6	10	24/22	38.5	25.7	28.6
6011-10-18.6-001	Cable Gland, PG11-10,BLACK	68	PG11	5-10	14-10	18.6	10	24/22	38.5	25.7	28.6
6011-10-18.6-012	Cable Gland, PG11-10,GRAY	68	PG11	5-10	14-10	18.6	10	24/22	38.5	25.7	28.6
6013.5-12.5-20.4-001	Cable Gland, PG13.5-12.5,BLACK	68	PG13.5	6-12.5	12-8	20.4	10	27/24	40.0	29.3	31.6
6013.5-12.5-20.4-012	Cable Gland, PG13.5-12.5,GRAY	68	PG13.5	6-12.5	12-8	20.4	10	27/24	40.0	29.3	31.6
6016-14-22.5-001	Cable Gland, PG16-14,BLACK	68	PG16	8.5-14	10-6	22.5	10.8	30/27	44.9	32.4	34.1
6016-14-22.5-012	Cable Gland, PG16-14,GRAY	68	PG16	8.5-14	10-6	22.5	10.8	30/27	44.9	32.4	34.1
6019-14-24-001	Cable Gland, PG19-14,BLACK	68	PG19	8.5-14	10-6	24	11	30/27	44.5	33.2	34.5
6019-14-24-012	Cable Gland, PG19-14,GRAY	68	PG19	8.5-14	10-6	24	11	30/27	44.5	33.2	34.5
6021-18-28.3-001	Cable Gland, PG21-18,BLACK	68	PG21	12.5-18	8-4	28.3	12	36-33	49.8	37.0	37.6
6021-18-28.3-012	Cable Gland, PG21-18,GRAY	68	PG21	12.5-18	8-4	28.3	12	36-33	49.8	37.0	37.6
6029-25-37-001	Cable Gland, PG29-25,BLACK	68	PG29	18-25	6-2	37	12	46/41	54.5	48.3	39.7
6029-25-37-012	Cable Gland, PG29-25,GRAY	68	PG29	18-25	6-2	37	12	46/41	54.5	48.3	39.7
6036-31-47-001	Cable Gland, PG36-31,BLACK	68	PG36	24-32	4 - 1/0	47	15	57/52	62.4	64.6	47.8
6036-31-47-012	Cable Gland, PG36-31,GRAY	68	PG36	24-32	4 - 1/0	47	15	57/52	62.4	64.6	47.8
6042-41-54-001	Cable Gland, PG42-41,BLACK	68	PG42	30-41	2 - 2/0	54	15	64/62	67.0	69.8	52.5
6042-41-54-012	Cable Gland, PG42-41,GRAY	68	PG42	30-41	2 - 2/0	54	15	64/62	67.0	69.8	52.5
6048-45-59.3-001	Cable Gland, PG48-45,BLACK	68	PG48	35-45	1/0 - 3/0	59.3	18.2	70/65	85.1	81.5	58.2
6048-45-59.3-012	Cable Gland, PG48-45,GRAY	68	PG48	35-45	1/0 - 3/0	59.3	18.2	70/65	85.1	81.5	58.2

Note: Cable outer diameter to AWG conversion is for reference only. Actual conductor size may vary depending on insulation thickness and cable construction.



CNC part number	ITEM DESCRIPTION	IP	Thread	Cable range	Cable Range AWG	C1 Thread O.D	C2 Thread Length	Spanner Size	L Total Length	C3 Max Diameter	L1 Length above Panel
6000-1/4-8-001	Cable Gland, NPT1/4-8,BLACK	68	NPT1/4"	4-8	16-12	13.2	8.5	19	29.7	20	21.2
6000-1/4-8-012	Cable Gland, NPT1/4-8,GRAY	68	NPT1/4"	4-8	16-12	13.2	8.5	19	29.7	20	21.2
6000-3/8-10-001	Cable Gland, NPT3/8-10,BLACK	68	NPT3/8"	5-10	14-10	16.7	10	22	39.3	25.1	30.1
6000-3/8-10-012	Cable Gland, NPT3/8-10,GRAY	68	NPT3/8"	5-10	14-10	16.7	10	22	39.3	25.1	30.1
6000-1/2-13-001	Cable Gland, NPT1/2-13,BLACK	68	NPT1/2	6-12.5	12-8	21.2	10	24	41.8	27	31.6
6000-1/2-13-012	Cable Gland, NPT1/2-13,GRAY	68	NPT1/2	6-12.5	12-8	21.2	10	24	41.8	27	31.6
6000-3/4-18-001	Cable Gland, NPT3/4-18,BLACK	68	NPT3/4	12.5-18	8-4	26.3	15	33	52	36.8	36.5
6000-3/4-18-012	Cable Gland, NPT3/4-18,GRAY	68	NPT3/4	12.5-18	8-4	26.3	15	33	52	36.8	36.5
6000-1-25-001	Cable Gland, NPT1-25,BLACK	68	NPT1	18-25	6-2	33.3	17	41	59.6	45.5	42.7
6000-1-25-012	Cable Gland, NPT1-25,GRAY	68	NPT1	18-25	6-2	33.3	17	41	59.6	45.5	42.7
6000-11/4-31-001	Cable Gland, NPT11/4-31,BLACK	68	NPT11/4"	24-32	4 - 1/0	41.9	17	52	64.3	54.6	47.3
6000-11/4-31-012	Cable Gland, NPT11/4-31,GRAY	68	NPT11/4"	24-32	4 - 1/0	41.9	17	52	64.3	54.6	47.3

Note: Cable outer diameter to AWG conversion is for reference only. Actual conductor size may vary depending on insulation thickness and cable construction.